




## ACCESORIOS DE FUNDICIÓN DÚCTIL BRIDA ORIENTABLE



### Brida Liso

- Dimensión según norma UNE-EN 545
- Presión de Trabajo; PN10, PN16 y PN25

CÓDIGO	DN	d	e	L	PESO (kg)		
					PN10	PN16	PN25
<b>04060080</b>	80	98	7,0	1000	7,7	8,2	9,2
<b>04060100</b>	100	118	7,2	1000	9,4	10,5	12,7
<b>04060125</b>	125	144	7,5	1000	12	13,7	16,02
<b>04060150</b>	150	170	7,8	1000	15,3	16,9	19,9
<b>04060200</b>	200	222	8,4	1000	22	24,9	32,1
<b>04060250</b>	250	274	9,0	1000	31,7	35,2	44,8
<b>04060300</b>	300	326	9,6	1000	43	46,8	56,2
<b>04060350</b>	350	378	10,2	1000	56,7	62,7	74,7
<b>04060400</b>	400	429	10,8	1000	70,1	77,8	93,2
<b>04060450</b>	450	480	11,4	1000	84,8	91,5	104,9
<b>04050500</b>	500	532	12,0	1000	112,1	118,4	131
<b>04050600</b>	600	635	13,2	1000	162,7	163,8	166