




## ACCESORIOS DE FUNDICIÓN DÚCTIL BRIDA ORIENTABLE



### Cruz de bridas

- Dimensión según norma UNE-EN 545
- Presión de Trabajo; PN10, PN16 y PN25

CÓDIGO	DN	dn	e <sub>1</sub>	e <sub>2</sub>	H	L	PN10	PN16	PESO (kg)	
							DA	DA	PN10	PN16
<b>04260050</b>	50	50	7,0	7,0	135	280	99	99	14	14
<b>04260065</b>	65	65	7,0	7,0	150	300	108	108	13,1	13,1
<b>04260080</b>	80	80	7,0	7,0	165	330	132	132	20,7	20,7
<b>04260100</b>	100	100	7,2	7,2	180	360	156	156	24,0	24,0
<b>04260125</b>	125	125	7,5	7,5	200	400	184	184	28,2	28,2
<b>04260150</b>	150	150	7,8	7,8	220	440	211	211	32,0	32,0
<b>04260200</b>	200	200	8,4	8,4	260	520	266	266	43,0	43,0
<b>04260250</b>	250	250	9,0	9,0	350	700	319	319	62,0	62,0
<b>04260300</b>	300	300	9,6	9,6	400	800	370	370	115,5	119,5
<b>04260400</b>	400	400	10,8	10,8	450	900	480	480	230	233